

Reliable ® Jib Crane Rightway® Winch 1234 Washington Street, Boston, MA 02118 PHONE: 617-482-8383 - FAX: 617-482-8384

Toll-Free: 800-321-3236 WEB SITE: www.ac-h.com WINCH QUOTE REQUEST

O DISTRIBUTOR O END USER

Company	Date
Name	Phone Number
Address	Fax Number
City State Zip Cod	e — e-mail
Winch Rated Capacity single line (lbs.)	Speed Single Line(FPM)
Maximum actual feet of lift or pull with full rated load (Ft.) Wire Rope Size (diameter)	
When drum capacity desired is greater than maximum len	gth of lift or pull, advise us same is for additional rope storage purposes only.
Winch will be used for:	Pulling Electrical brake required
Duty Cycle Operating Time:	
Minutes Per Hour Hours per Da	Days Per Week
Power Supply:	
C Electric Voltage Phase Hz	
CFM @ P.S.I.	
Controls: Mounting:	
Magnetic Remote Pushbutton	○ Horizontal Base ○ Vertical ○ Inverted Ceiling
C Lever Drum Mounted at Winch	
Operati	onal Environment:
Outdoor Service Indoor Service	Extreme Temperature Low
Explosive Gases Dusty or Abrasive Atmosphere	
<u>IMPORTANT</u> High	
Type of Application and Operation (Please provide as much detail as possible)	